

Contents

Technical Committee on Mechanical Refrigeration Code vi

Preface ix

1 Scope 1

- 1.1 Purpose 1
- 1.2 Application 1
- 1.3 Mandatory language 1
- 1.4 Units of measurement 2

2 Reference publications 2

3 Definitions and abbreviations 3

- 3.1 Definitions 3
- 3.2 Abbreviations 7

4 System selection and application requirements 8

- 4.1 Application procedure 8
- 4.2 Classification by occupancy 8
 - 4.2.1 General 8
 - 4.2.2 Institutional occupancy 8
 - 4.2.3 Public assembly occupancy 8
 - 4.2.4 Residential occupancy 9
 - 4.2.5 Commercial occupancy 9
 - 4.2.6 Industrial occupancy 9
 - 4.2.7 Mixed occupancy 9
 - 4.2.8 Adjacent locations 9
- 4.3 Classification of refrigeration systems 9
 - 4.3.1 Classification by type 9
 - 4.3.2 Classification by leakage probability 12
- 4.4 Classification by refrigerant 12
- 4.5 System application requirements 16
 - 4.5.1 General 16
 - 4.5.2 System application rules 17
 - 4.5.3 Equipment applied in a high-probability system 18
- 4.6 Additional requirements for institutional, public assembly, residential, and commercial occupancies 18
 - 4.6.1 Public stairway, stair landing, or exit 18
 - 4.6.2 Public hallway or lobby 18

5 Equipment design and construction 18

- 5.1 Drawings, specifications, and data reports 18
- 5.2 Refrigeration systems rated 125 kW or less 19
- 5.3 Filing of drawings 19
 - 5.3.1 Submission of drawings and specifications 19
 - 5.3.2 Contents of drawings 19
- 5.4 Materials 19
- 5.5 Design pressures 20
- 5.6 Refrigerant-containing pressure vessels 23
- 5.7 Refrigerant piping, fittings, evaporator and condenser coils, and associated headers 23
 - 5.7.1 Refrigerant piping and fittings 23

5.7.2	Minimum requirements for unprotected refrigerant piping and tubing	24
5.7.3	Evaporator and condenser coils and associated headers	24
5.8	Components other than pressure vessels, piping, and fittings	25
5.9	Design provisions for service	25
5.10	Pressure testing	26
5.10.1	General	26
5.10.2	Test medium	26
5.10.3	Factory tests	26
5.10.4	Field tests	27
5.11	Marking and labelling	27
5.11.1	Signs (all systems)	27
5.11.2	Nameplates for unit systems, condensing units, compressors, and compressor units	27
5.11.3	Signs for systems containing more than 45 kg (100 lb) of refrigerant	28
5.11.4	New signs for changed refrigerant	28
5.11.5	Posting of instructions	28
5.12	Substitution of refrigerant type	28
6	Installation	29
6.1	General	29
6.2	Machinery rooms	29
6.2.1	General	29
6.2.2	Doors	29
6.2.3	Refrigerant vapour detector	30
6.2.4	Explosion protection	30
6.2.5	Ventilation	30
6.3	Class T machinery rooms	32
6.4	Machinery rooms — Electrical requirements for ammonia systems	32
6.4.1	Class T machinery rooms	32
6.4.2	Machinery rooms	32
6.5	Water supply and discharge connections	33
6.6	Electrical wiring	33
6.7	Gas devices	33
6.8	Location of refrigerant piping	33
6.9	Joints and refrigerant-containing parts in air ducts	34
6.10	Emergency discharge	34
6.11	Purge discharge	34
7	Overpressure protection	34
7.1	Pressure vessel protection	34
7.1.1	ASME <i>Boiler and Pressure Vessel Code</i> requirements	34
7.1.2	Pressure vessels with an internal gross volume of 0.085 m ³ (3 ft ³) or less	34
7.1.3	Pressure vessels with an internal gross volume exceeding 0.085 m ³ (3 ft ³)	34
7.1.4	Pressure-relief devices for pressure vessels used as, or as part of, evaporators	35
7.2	System protection	35
7.2.1	Pressure-limiting devices	35
7.2.2	Setting of pressure-limiting devices	35
7.2.3	Positive-displacement compressor protection	36
7.2.4	Expansion of liquid refrigerant	36
7.3	Pressure-relief devices	36
7.3.1	General	36
7.3.2	Location of pressure-relief devices	37
7.3.3	Setting of pressure-relief devices	37
7.3.4	Capacity of pressure-relief devices	38
7.3.5	Marking of fusible plugs and other pressure-relief devices	40
7.3.6	Discharge of fusible plugs and other pressure-relief devices	40

8 Maintenance of systems 56

- 8.1 Charging and withdrawal of refrigerants 56
- 8.2 Refrigerants withdrawn from refrigeration systems 56
- 8.3 Refrigerant storage 56
- 8.4 Maintenance 56

9 Precautions 57

- 9.1 Protective equipment 57
- 9.2 Enclosed spaces 57

Annexes

- A** (informative) — Maximum allowable concentration of mixtures 58
- B** (informative) — Guidelines for emergency discharge of refrigerants 59
- C** (informative) — Worst-case composition of fractionation 61
- D** (informative) — Conversion factors 62
- E** (informative) — A method for calculating the discharge capacity of pressure-relief devices for positive displacement compressors 63
- F** — Reserved 65
- G** — Reserved 66
- H** (normative) — Allowable equivalent length of discharge piping 67
- I** (informative) — CSA B52 Information Bulletin on use of hydrocarbon refrigerants in new equipment and as drop-in replacements for other classes of refrigerants in existing systems 69

Index 72

Tables

- 1** — Refrigerant classifications and quantities 13
- 2** — System application requirements 16
- 3** — Maximum permissible quantities of refrigerants for high-probability systems 18
- 4** — Minimum design pressures 21
- 5** — Unprotected soft annealed copper tubing — Minimum nominal wall thickness 24
- 6** — Discharge capacity calculation factor, f , for refrigerants 39
- 7** — Pressure-relief valve discharge line capacity (lb/min of air) for various equivalent discharge line lengths for steel (expressed in imperial units) 42
- 8** — Pressure-relief valve discharge line capacity (lb/min of air) for various discharge line lengths for copper (expressed in imperial units) 49

Figures

- 1** — Flow diagram for identification of systems requirements 8
- 2** — Direct system 10
- 3** — Double direct system 10
- 4** — Indirect system 11
- 5** — Matrix of refrigerant classifications 12