

Contents

	Page
Foreword	vii
1.3 Design and application	1
1.3.1 Scope	1
1.3.2 Preferred units for pump applications	1
1.3.3 Typical applications	1
1.3.3.1 Booster service	1
1.3.3.2 Process service (chemical, petrochemical, injection)	1
1.3.3.3 Transfer pumping	4
1.3.3.4 Mine dewatering	4
1.3.3.5 Well pumping	4
1.3.3.6 Irrigation service	4
1.3.3.7 Pumps for steam power plants	4
1.3.3.8 Fire pumps	10
1.3.3.9 Pumps used as hydraulic turbines	11
1.3.3.10 General purpose service	13
1.3.3.11 Wastewater service (solids and non-clog)	14
1.3.3.12 Pulp and paper applications	15
1.3.3.13 Slurry service	17
1.3.3.14 Liquids with vapor or gas	19
1.3.4 Performance, selection criteria	21
1.3.4.1 System requirements	21
1.3.4.2 Determination of operating duty	42
1.3.4.3 Efficiency prediction method for centrifugal pumps	49
1.3.4.4 Operation away from the best efficiency point	56
1.3.4.5 Noise levels	57
1.3.4.6 Suction conditions	57
1.3.4.7 Mechanical features	58
1.3.4.8 Impeller types	75
1.3.4.9 Casing type	76
1.3.4.10 Drivers: type and size	76
1.3.4.11 Pump liquid temperature limits on end suction pumps	78
1.3.5 Horizontal pump baseplate design	78
1.3.5.1 Introduction	78
1.3.5.2 Functional requirements	79
1.3.5.3 Definitions	79
1.3.5.4 Tolerancing	80
1.3.5.5 Shims and fasteners	81
1.3.5.6 Stress levels	81

1.3.5.7	Rigidity	84
1.3.5.8	Miscellaneous criteria	84
Appendix A	Torsional Stiffness	86
Appendix B	Recommended Equipment Mounting Drilling Dimensions	87
Appendix C	References	88
Appendix D	Index	89

Figures

1.47	— Diagram of a simple steam power cycle	5
1.48	— Diagram of a typical condensing steam power plant	5
1.49	— Diagram of a closed feedwater cycle	7
1.50	— Diagram of an open feedwater cycle with one deaerator and three closed heaters	7
1.51	— Turbine characteristics	11
1.52	— Turbine performance	12
1.53	— Self-priming pump — construction industry	14
1.54	— Self-priming pump — chemical industry	15
1.55	— Nomograph of the relationship of concentration to specific gravity in aqueous slurries	18
1.56	— Typical performance characteristics — non-settling slurries	19
1.57	— Typical performance characteristics — settling slurries	19
1.58	— Effect of gas on pump performance	20
1.59	— Inducer	20
1.60	— Venting the eye of the impeller	21
1.61	— Top suction impeller	21
1.62	— Pump versus system	21
1.63	— Torque curve	23
1.64A	— Performance correction chart for viscous liquids (metric)	24
1.64B	— Performance correction chart for viscous liquids (US units)	25
1.65A	— Performance correction chart for viscous liquids (metric)	26
1.65B	— Performance correction chart for viscous liquids (US units)	27
1.66A	— Sample performance chart (Metric)	30
1.66B	— Sample performance chart (US Units)	31
1.67A	— Recommended typical operating speed limits for single suction pumps (metric)	33
1.67B	— Recommended typical operating speed limits for single suction pumps (US units)	34
1.68A	— Recommended typical operating speed limits for double suction pumps (metric)	35

1.68B — Recommended typical operating speed limits for double suction pumps (US units)	36
1.69A — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (metric).	40
1.69B — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (US units).	41
1.70 — Pumps operating in series	42
1.71 — Pumps operating in parallel	42
1.72A — Pump performance (Metric)	44
1.73A — Temperature rise (Metric)	44
1.72B — Pump performance (US Units)	44
1.73B — Temperature rise (US Units)	45
1.74 — Impeller with angled outside diameter	49
1.75A — Optimum generally attainable efficiency chart (Metric)	50
1.75B — Specific speed-efficiency correction chart (Metric)	50
1.75C — Optimum generally attainable efficiency chart (US Units).	51
1.75D — Specific speed-efficiency correction chart (US Units)	51
1.76A — Deviation from generally attainable efficiency (Metric)	52
1.76B — Deviation from generally attainable efficiency (US Units)	52
1.77A — Estimated efficiency increase due to improved surface finish (Metric)	54
1.77B — Estimated efficiency increase due to improved surface finish (US Units)	54
1.78A — Estimated efficiency decrease due to increased wear ring clearance (Metric)	55
1.78B — Estimated efficiency decrease due to increased wear ring clearance (US Units)	55
1.79 — Inducer.	57
1.80 — Single volute casing.	58
1.81 — K versus rate of flow for single volute casing	59
1.82 — Dual (double) volute casing	59
1.83 — K versus rate of flow for dual (double) volute casing	59
1.84 — Circular casing.	60
1.85 — Pressure distribution on enclosed impeller shrouds	60
1.86 — Enclosed impeller with plain back shroud	61
1.87 — Impeller with back ring.	62
1.88 — Mechanical seal classifications	69
1.89 — Stuffing-box without lantern ring	69
1.90 — Stuffing-box with lantern ring.	70
1.91 — Overhung impeller	71
1.92 — Impeller between bearings	72
1.93 — Grouted baseplate	79

1.94 — Free-standing baseplate	79
1.95 — Height of mounting surfaces	81
1.96 — Equipment mounting surface flatness	81
1.97 — Motor mounting pads	81
1.98 — Mounting block dimensions	85
A.1 — Baseplate support and anchoring	86
B.1 — Recommended equipment mounting drilling dimensions	87

Tables

1.3.1 — Symbols	2
1.3.2 — Subscripts	3
1.3.3A — Sample calculations (Metric)	30
1.3.3B — Sample calculations (US Units)	32
1.3.4 — The influence of pump type on efficiency	56
1.3.5 — Rolling element bearing types	64
1.3.6 — Product lubricated sleeve bearing material selection guide (commonly used in vertical turbine pumps)	66
1.3.7 — Guidelines for minimum and maximum pump liquid temperature for cast grey iron and ductile iron pumps (°C)	78
1.3.8 — Guidelines for minimum and maximum pump liquid temperature for cast grey iron and ductile iron pumps (°F)	78
1.3.9 — Metric manufacturing tolerances	80
1.3.10 — US units manufacturing tolerances	80