

American Nuclear Society


WITHDRAWN

August 23, 2001
ANSI/ANS-6.4.3-1991

**gamma -ray attenuation coefficients and
buildup factors for engineering materials**

an American National Standard

**No longer being maintained as
an American National Standard.
This standard may contain
outdated material or may have
been superseded by another
standard. Please contact the
ANS Standards Administrator for
details.**



published by the
American Nuclear Society
555 North Kensington Avenue
La Grange Park, Illinois 60526 USA

ANSI/ANS-6.4.3-1991

**American National Standard
for Gamma-Ray Attenuation Coefficients and
Buildup Factors for Engineering Materials**

Secretariat
American Nuclear Society

Prepared by the
**American Nuclear Society
Standards Committee
Working Group ANS-6.4.3**

Published by the
**American Nuclear Society
555 North Kensington Avenue
La Grange Park, Illinois 60525 USA**

Approved August 26, 1991
by the
American National Standards Institute, Inc.

American National Standard

Designation of this document as an American National Standard attests that the principles of openness and due process have been followed in the approval procedure and that a consensus of those directly and materially affected by the standard has been achieved.

This standard was developed under the procedures of the Standards Committee of the American Nuclear Society; these procedures are accredited by the American National Standards Institute, Inc., as meeting the criteria for American National Standards. The consensus committee that approved the standard was balanced to ensure that competent, concerned, and varied interests have had an opportunity to participate.

An American National Standard is intended to aid industry, consumers, governmental agencies, and general interest groups. Its use is entirely voluntary. The existence of an American National Standard, in and of itself, does not preclude anyone from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standard.

By publication of this standard, the American Nuclear Society does not insure anyone utilizing the standard against liability allegedly arising from or after its use. The content of this standard reflects acceptable practice at the time of its approval and publication. Changes, if any, occurring through developments in the state of the art, may be considered at the time that the standard is subjected to periodic review. It may be reaffirmed, revised, or withdrawn at any time in accordance with established procedures. Users of this standard are cautioned to determine the validity of copies in their possession and to establish that they are of the latest issue.

The American Nuclear Society accepts no responsibility for interpretations of this standard made by any individual or by any ad hoc group of individuals. Requests for interpretation should be sent to the Standards Department at Society Headquarters. Action will be taken to provide appropriate response in accordance with established procedures that ensure consensus on the interpretation.

Comments on this standard are encouraged and should be sent to Society Headquarters.

Published by

American Nuclear Society
555 North Kensington Avenue, La Grange Park, Illinois 60525 USA

Copyright © 1992 by American Nuclear Society.

Any part of this standard may be quoted. Credit lines should read "Extracted from American National Standard ANSI/ANS-6.4.3-1991 with permission of the publisher, the American Nuclear Society." Reproduction prohibited under copyright convention unless written permission is granted by the American Nuclear Society.

Printed in the United States of America

Foreword (This foreword is not a part of American National Standard for Gamma-Ray Attenuation Coefficients and Buildup Factors for Engineering Materials, ANSI/ANS-6.4.3-1991.)

It came to the attention of Subcommittee ANS-6, Radiation Protection and Shielding, of the American Nuclear Society Standards Committee, following the 1979 Three-Mile Island accident, that gamma-ray attenuation data for several needed materials, especially for the lower energies, was lacking. It was also known by the subcommittee that data available in the literature are not always in good agreement. Therefore, it was felt by the subcommittee that an evaluated standard reference data set would be useful to engineers involved in radiation accident response as well as for routine shield design.

During 1980, Working Group ANS-6.4, charged with the oversight of standards on shielding materials, organized a meeting to consider developing the needed standard. At this meeting the first scope was drafted and a decision made that a new working group, later designated ANS-6.4.3, be formed to develop the proposed standard. Following this meeting, a chairman was identified and members with special expertise and experience were recruited.

Early in the work, the group decided that the best set of available buildup factors were those computed at the National Bureau of Standards, now the National Institute of Standards and Technology (NIST), only a fraction of which had been published. These covered a broad energy range and covered the range of materials needed from atomic number 4 (Be) to 92 (U). Before accepting the data, however, the group undertook a validation process by making Monte Carlo and other transport theory calculations and comparing with reported values in the literature. During the validation process many changes were made, and data for additional materials were obtained from calculations performed in Japan and India. In 1989, the buildup factors for the heavy elements (Mo and above) were recalculated in Japan to make use of the latest cross section data and to obtain detailed results above the absorption edges.

In view of the fact that there are several standard gamma-ray response functions and the whole subject is under review by the International Commission on Radiological Protection, the working group that developed American National Standard for Neutron and Gamma-Ray Fluence-to-Dose Factors, ANSI/ANS-6.1.1-1991, and others, the group decided to present exposure and energy absorption buildup factors.

It was recognized by the working group that most uses of buildup factors are for point kernel calculations that assume radiation leakage from a shield and energy absorption in a phantom. This configuration is a significant departure from the infinite medium that is assumed when determining the buildup factors, especially in the case of a heavy-element shield such as lead. Therefore, a table of correction factors is presented to provide a means of taking this into account. Data for correcting the buildup factors for coherent scattering became available in 1989, and tables for this purpose have also been added to the standard.

The attenuation and energy absorption coefficients were relatively easy to obtain; they were obtained from published and unpublished data of the NIST Photon and Charged-Particle Data Center, a unit of the National Standard Reference Data System.

The membership of Working Group ANS-6.4.3 is as follows:

D. K. Trubey, Chairman, *Oak Ridge National Laboratory*
C. M. Eisenhauer, *National Institute of Standards and Technology*
A. Foderaro, *Pennsylvania State University (retired)*
D. V. Gopinath, *Bhabha Atomic Research Centre, India*
Y. Harima, *Tokyo Institute of Technology, Japan*
J. H. Hubbell, *National Institute of Standards and Technology*
K. Shure, *Bettis Atomic Power Laboratory*
Shiaw-Der Su, *General Atomics*

The roster of ANS-6, Radiation Protection and Shielding, at the time of its approval of this standard was as follows:

D. K. Trubey, Chairman, *Oak Ridge National Laboratory*
E. T. Boulette, *Maine Yankee Atomic Power Company*
J. C. Celnik, *Consultant*
D. R. Harris, *Rensselaer Polytechnic Institute*
W. C. Hopkins, *Bechtel Power Corporation*
E. A. Normand, *Boeing Aerospace Company*
P. J. Persiani, *Argonne National Laboratory*

Consensus Committee N17, Research Reactors, Reactor Physics, Radiation Shielding, and Computational Methods, had the following membership at the time it reviewed and approved this standard:

T. M. Raby, Chairman
A. Weitzberg, Vice Chairman

J. D. Buchanan Individual
A. D. Callihan Individual
R. E. Carter Individual
D. Cokinos Brookhaven National Laboratory
A. De La Paz Vista Technology, Inc.
D. Duffey American Institute of Chemical Engineers
H. Goldstein American Physical Society
S. Hartzell Power Computing
P. B. Hemmig U.S. Department of Energy
J. W. Lewellen (Alt.)
W. A. Holt American Public Health Association
J. E. Hyder Health Physics Society
A. Johnson (Alt.)
L. I. Kopp Individual
J. E. Olhoeft Individual
T. M. Raby American Nuclear Society
W. J. Richards U.S. Department of Defense
M. M. Ter Pogossian American College of Radiology
J. F. Torrence National Institute of Standards and Technology
D. K. Trubey Oak Ridge National Laboratory
S. H. Weiss U.S. Nuclear Regulatory Commission
A. Adams, Jr. (Alt.)
A. Weitzberg NUS Corporation
W. L. Whittemore Individual

Contents	Section	Page
	1. Scope	1
	2. Definitions	1
	3. Sources of Data	2
	4. Applications of this Standard in Practice	3
	5. References	4

Tables

1. Mass Total Attenuation Coefficients		
1a. Mass Attenuation Coefficients (without coherent scattering)		6
1b. Mass Attenuation Coefficients (with coherent scattering)		9
1c. Mass Attenuation Coefficients (detailed energy grid for high-Z elements)		12
2. Mass Energy Absorption Coefficients		13
3. Exposure Buildup Factors		16
4. Energy Absorption Buildup Factors		42
5. Fitting Functions		
5.1 G-P (Geometric Progression) Buildup Factor Coefficients		68
5.2 Taylor Buildup Factor Coefficients		94
6. Elemental Compositions of Concrete and Air		107
7. Shield-Tissue Interface Correction Factors		108
8. Coherent Scattering Correction Factors		112

Gamma-Ray Attenuation Coefficients and Buildup Factors for Engineering Materials

1. Scope

This standard presents evaluated gamma-ray elemental attenuation coefficients and single-material buildup factors for selected engineering materials for use in shielding calculations of structures in power plants and other nuclear facilities. The data cover the energy range 0.015-15 MeV and up to 40 mean free paths (mfp). These data are intended to be standard reference data for use in radiation analyses employing point-kernel methods.

2. Definitions

Attenuation coefficient. Of a substance, for a parallel beam of specified radiation: the quantity μ , in the expression μdx for the fraction removed by attenuation in passing through a thin layer of thickness dx of that substance. It is a function of the energy of the radiation. As dx is expressed in terms of length, mass per unit area, moles or atoms per unit area, μ is called the linear, mass, molar, or atomic attenuation coefficient, respectively.

Energy absorption coefficient. Of a substance, for a parallel beam of specified radiation: the quantity μ_{en} in the expression $\mu_{en} dx$ for the fraction of energy absorbed in passing through a thin layer of thickness dx of that substance. It is a function of energy of the radiation. As dx is expressed in terms of length, mass per unit area, moles per unit area, or atoms per unit area, μ_{en} is called the linear, mass, molar, or atomic energy absorption coefficient.

Note: It is that part of the attenuation coefficient resulting from energy absorption only and is equal to the product of the energy transfer coefficient and $1 - g$, where g is the fraction of the energy of secondary charged particles that is lost to bremsstrahlung in the material.

Buildup factor. In the passage of radiation through a medium, the ratio of the total value of a specified radiation quantity at any point to the contribution to that value from radiation reaching the point without having undergone a collision.

Buildup factor, exposure, B_D . A photon buildup factor in which the quantity of interest is exposure. The energy response function is that of absorption in air.

Buildup factor, energy absorption, B_A . A photon buildup factor in which the quantity of interest is the absorbed or deposited energy in the shield medium. The energy response function is that of absorption in the material.

Correction factor, shield-tissue interface. A correction factor to be applied to the basic infinite-medium exposure buildup factor to correct for the scattering in a tissue phantom after emerging from a shield.

Fitting function, Taylor. A buildup factor function of distance from the source in the form:

$$B(E,x) = A_1 \exp(-a_1 x) + A_2 \exp(-a_2 x) \quad (1)$$

where x is the distance from the source in mean free paths and parameters A_1 , a_1 , and a_2 are functions of the attenuating medium and the source energy, E . The fourth parameter, A_2 , is constrained to equal $1 - A_1$.

Fitting function, G-P (Geometric Progression). A buildup factor function of distance from the source in the form:

$$\begin{aligned} B(E,x) &= 1 + (b-1)(K^x - 1)/(K-1) \text{ for } K \neq 1 \text{ and} \\ B(E,x) &= 1 + (b-1)x \text{ for } K = 1. \end{aligned} \quad (2)$$

$$K(E,x) = cx^a + d [\tanh(x/X_k - 2) - \tanh(-2)] / [1 - \tanh(-2)], \quad (3)$$

where x is the distance from the source in mean free paths and b is the value of the buildup factor at 1 mfp. The variation of parameter K with penetration represents the photon dose multiplication and change in the shape of the spectrum from that at 1 mfp, which determined the value of b . Equation (3) represents the dependence of K on x ; a , c , d , and X_k are fitting parameters that